



Standard Technical Specifications

Hull length	13,99 m / 45'11"
Length overall (with options)	14,50 m / 47'7"
Beam	7,96 m / 26'1"
Air draft	23,21 m / 76'2"
Draft	1,37 m / 4'6"
Displacement (CE)	16,3 T / 35,942 Lbs
Upwind sail area (standard mainsail)	123 m ² / 1,323 sq.ft
Upwind sail area (optional mainsail)	127 m ² / 1,367 sq.ft
Full battened mainsail (standard)	76,5 m ² / 823 sq.ft
Square top mainsail (option)	80,5 m ² / 866 sq.ft
Self-tacking jib	46,5 m ² / 500 sq.ft
Code 0 (option)	105 m ² / 1,130 sq.ft
Fresh water capacity (max.)	600 L / 159 US gal
Fuel capacity	1,040 L / 275 US gal
Engines	2 x 57 CV / HP YANMAR
Architects	VPLP Design
Exterior design	Patrick le Quément
Interior design	Nauta Design
Number of berths	6 à 12
CE certification	A : 12 - B : 14 - C : 20 - D : 30

North American Specifications

ONLY FOR BOATS SOLD IN US

- 110V electric panel and electric equipment
- US 110V outlets
- Gas propane circuit with solenoid valve

Construction

- Polyester and high quality anti-osmotic resin
- Hull, deck and coachroof laminated by infusion
- Balsa core hull and deck, white gel coat
- Laminated or glued plywood

Steering gear

- 2 suspended rudder blades
- Hydraulic steering transmission
- Emergency tiller

Sails and rigging

SAILS

- High roach mainsail in Dacron with battens
- Self-tacking jib in Dacron with UV protective band

STANDING RIGGING

- Anodized aluminium mast on the roof
- Anodized aluminium boom
- 1 spreader rig
- Coated shrouds
- Furling forestay for self-tacking jib
- 2 forestay chainplates and 1 shroud chainplates
- Adjustable lazy-jacks

RUNNING RIGGING

- Mainsail halyard
- Self-tacking jib halyard
- Mainsheet
- Self-tacking jib sheet
- 3 reefing lines
- Self-tacking jib furling line
- Mainsheet traveler lines
- Boom uphaul
- Mainsheet fuse

Hardware

- 2 manual winches size 50.2 STA
- 1 manual winch size 40.2 STA
- Footblocks & clutches for halyards, reefing lines and sheets
- Mainsail track and ball-bearing car
- Track and car for self-tacking jib sheet with stopper
- Anodized aluminium crossbeam with fixing point for the self-tacking jib furler, and anchor roller

Mooring

- Composite longitudinal crossbeam with integrated chain run and mooring cleat
- 8 mooring cleats
- 1700W / 12V electrical windlass with vertical axis, chain 10 mm

Engines

- 2 diesel engines YANMAR 4JH57 57CV SailDrive
- Fixed three blade propeller
- Sea water filter
- Mechanical engine throttles at the helm station
- Engine compartment ventilation: 12V electrical extraction in the aft transom
- Fuel circuit:
 - 2 rotomoulded tanks of 520L / 137 US gal
 - Fuel filter systems
 - Fuel shut off valve
 - Gauge at the general control panel on touch screen

Plumbing

FRESH WATER CIRCUIT

- Fresh water tank: 600L / 159 US gal with gauge at the chart table
- Fresh water circuit with 1 main water group 18,5L/mn
- Hot water circuit with 60L / 16 US gal water heater and engine exchanger

GREY WATER CIRCUIT

- Shower and sink draining by automatic water sensor with timer
- Grey water drainage cockpit and salon direct to the sea

BLACK WATER CIRCUIT

- Black water holding tanks:
 - 3-cabin, 3 heads version: 2 x 120L (240L / 63 US gal)
 - 4-cabin, 4 heads version: 2 x 120L (240L / 63 US gal)
- Tank drain by gravity or deck plate

BILGE PUMP CIRCUIT

- 1 manual bilge pump per hull
- 1 automatic immersed bilge pump per hull, with alarm signal
- Self-draining cockpit compliant to the CE certifications

Electrical

- Seanapps® connectivity - Battery voltage and GPS position on mobile app

DC POWER CIRCUIT - 12V

- 2 harnessed alternators 125A
- 2 engine batteries 50A (AGM)
- 3 service batteries 140A (AGM)
- Battery circuit breakers in the engine compartments

DISTRIBUTION ELECTRIC PANEL

- General control panel 12V at chart table
- USB sockets 12V included in the electrical panel

LIGHTING

- 12V LED interior lighting and reading lights
- 12V lighting in engine compartment
- LED navigation lights
- Deck light on mast

Deck layout

TRANSOM

- Hot/cold deck shower on portside
- S/S telescopic swim ladder with fixed handles on portside
- Storage on the sides of the transoms (port and starboard)

AFT COCKPIT

- L-shaped bench on portside
- Polyester cockpit table
- Exterior furniture on portside:
 - Corian® countertop
 - Storage
 - Gas locker
 - Bin
- Exterior furniture on starboard:
 - Corian® countertop
 - Double door with shelves
 - Tray and cup holders
- Lounger with locker on starboard
- Composite aft beam:
 - Seats
 - Liferaft
- Cockpit flush-decked with saloon
- Composite non-streaming toe rails on cockpit sides
- Non-slip cockpit floor
- Self-draining cockpit with wooden grating

FLYBRIDGE

- Access from the cockpit and deck
- Double helm seat
- Leather covered steering wheel ø800mm
- Engine throttles and panel
- Console for screen and instrumentation
- Storage bag for halyards

FORWARD COCKPIT

- U-shaped seating area
- Large hatches for technical access
- Nylon netting

BOW LOCKERS

- Access through LEWMAR T60 deck hatches
- Wooden floor
- LED lighting

STANCHIONS AND LIFELINES

- Pushpits: H610 mm / 24in
- 8 stanchions: H610 mm / 24in
- Double S/S lifelines

Interior layouts

GENERAL

- Construction in Alpi Sand Oak plywood, horizontal grain
- Laminated floor: Fortezza
- 100% recycled upholstery, adapted to the marine environment
- Ceiling and hull linings in padded PVC foam
- Eco-Cleaning Pack
- Furniture interiors in Okoumé finish

GALLEY

- Corian® countertop
- Port side:
 - U-shaped galley
 - Large s/s sink with Corian® cover
 - Hot/cold mixer tap
 - 3-burner gas stove
 - Gas oven
 - 12V 130L / 34 US gal refrigerator
- Low and high storage lockers with shelves and drawers

SALON

- L-shaped sofa
- Wooden dining table
- Fixed bench and 1 stool
- Lockers under the sofa
- Chart table with control panel and storage

OWNER'S CABIN

- Double bed with lateral access (2,00 x 1,60 m / 6'7" x 5'3")
- Treated cellular foam mattress
- Bedside shelves
- Under bed storage
- Storage units with shelves, drawers and wardrobe
- Sofa
- Desk
- T44 and T10 opening flush deck hatches
- Fixed hull window in PMMA with integrated opening portholes and roller blind

OWNER'S HEAD

- Private access from the Owner's cabin
- Composite countertop
- Integrated sink with hot/cold mixer tap
- High and low-level storage units
- Separated shower with PMMA door
- Manual toilet
- T44 and T10 opening flush deck hatches
- Fixed hull window in PMMA with integrated opening porthole

AFT CABINS

- Double bed with lateral access (2,00 x 1,60 m / 6'7" x 5'3")
- Treated cellular foam mattress
- Under bed storage
- Storage units with shelves, drawers and wardrobe
- T44 opening flush deck hatch
- Fixed hull window in PMMA with integrated opening portholes and roller blind

FORWARD CABINS

- Double bed with lateral access (2,00 x 1,60 m / 6'7" x 5'3")
- Treated cellular foam mattress
- Under bed storage
- Storage units with shelves and wardrobe
- T44 opening flush deck hatch
- Fixed hull window in PMMA with integrated opening portholes and roller blind

HEADS

- Corian® countertop
- Integrated sink with hot/cold mixer tap
- High and low-level storage units
- Separated shower with PMMA door
- Manual toilet
- T10 opening flush deck hatch



162, quai de Brazza CS 81217
33072 Bordeaux Cedex - France
Tél. 33 + (0) 557 80 92 80
E-mail : info@cata-lagoon.com
www.cata-lagoon.com